

Rubio Monocoat UNIVERSAL MAINTENANCE OIL

**0%
VOC**

DESCRIPTION:

Rubio Monocoat Universal Maintenance Oil is universal maintenance oil used for protecting and refreshing the color of oiled wooden surfaces. The maintenance frequency depends on the intensity of the floor traffic. It is advisable to apply this treatment just before the colour fades.

RMC Universal Maintenance Oil will nourish the wood, give it a fuller look (satin sheen) and increase the fluid resistance.

Maintenance with the **RMC Oil Plus 2C** in its original colour should be done when the treated surface starts to show too much wear and tear or if the colour needs to be repaired.

INSTRUCTIONS:

No professional expertise is required to treat your floor with **RMC Universal Maintenance Oil**.

1. Eliminate dirt and dust from the floor.
2. Clean the floor thoroughly with **RMC Soap** and water. Rinse well with water to eliminate any soap residues. Leave it to dry completely.
3. Manual application – Apply the oil using a cloth, brush, or sponge. Mechanical application – Apply the oil using a floor polisher and a beige colored pad. Treat areas of preferably 2 to 4 m². Each treated area should be wiped dry using kitchen tissue or a cotton cloth within 15 minutes. When using a floor polisher, wipe dry using a white pad.
4. Ensure the room is well-ventilated. The floor should be dry after 6 - 8 hours.

During the first week clean only using a wet cloth. Later, **RMC Soap** may be used.

COVERAGE:

0,5 l = 75 – 100 m² (depending on wear)

Use very little product to prevent the floor from becoming sticky.

These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.

TECHNICAL SPECIFICATIONS:

Basis: a mixture of natural oils and hard wax

Consistency: liquid

Flash point cc (astm d93): > 65 °C

Density: 0.93 - 1.4 g/cm³

VOC: 0 g/L

STORAGE:

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging.

PACKAGING:

Can 0,5 L

WARNING:

The product may NOT be diluted!
Cloths, saturated with oil, may spontaneously combust.
After usage, they need to be soaked in water before disposal.

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.

Date TDS: 22/08/16

MUYLLE FACON



MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)

Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823

info@muyllefacon.be - www.rubiomonocoat.com

