



2330 G3 M73 PW19 3600-840 ETDD

Recessed LED luminaire

TOC: 7631751



Product description

Luminaire type

Square recessed LED ceiling luminaire with prismatic PMMA cover.

Applications

Offices, Corridors, Foyers, Conference rooms, Retail areas, waiting zones.

Mounting methods

For system ceilings with exposed grids. Version M73. For system dimension 600 mm x 600 mm.

Optical system

PMMA cover with microprisms. With narrow-wide light distribution. Glare evaluation (EN 12464-1) according to UGR < 19. Suitable for VDU workstations according to EN 12464-1 via limited luminance $L \leq 3000 \text{ cd/m}^2$ for beam angle above 65° all-round. Harmonious light effect due to homogeneously illuminated light emission.

LED system

Luminaire luminous flux 3600 lm, connected load 31,00 W, luminous efficiency of luminaire 116 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI) $R_a > 80$. Mean rated service life $L65(t_q 25^\circ\text{C}) = 50,000 \text{ h}$.

Luminaire body

Luminaire body of aluminium. Surface coated white (RAL 9016).

Electrical version

With electronic transformer, digitally dimmable (DALI). The luminaire complies with fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

Light management

The luminaire is DALI-dimmable and can be integrated into the TRILUX LiveLink light management system.

Product features and key data

Applications	offices corridors foyers conference rooms sales rooms waiting zones
Luminaire type	Square recessed LED ceiling luminaire with prismatic PMMA cover.
Mounting method	Recessed
Luminaire optic	PMMA cover with microprisms.
Connected load	31 W
Colour temperature	4.000 K
Rated luminous flux	3.600 lm
Luminous efficacy	116 lm/W
Service life	L65 (25 °C) = 50.000 h
Colour rendering index	80
Colour tolerance	5 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body of aluminium.

Product features and key data

Electrical version	With electronic transformer, digitally dimmable (DALI).
Connection method	Terminal
Touch-Dim-capable	Yes
Mains frequency	50/60 Hz
Mains voltage	220 - 240 V
Total harmonic distortion < %	14 %
Ingress Protection (IP) rating	IP20
Protection rating on room side	IP40
Protection class	I
Impact resistance (IK)	IK02
Hot wire resistance	650 °C
Ambient temperature	25 °C
Net length	595 mm
Net width	595 mm
Net height	65 mm
Recess length	595 mm
Recess width	595 mm
Recess depth	190 mm
Weight	2,0 kg

Available accessories

Material	Description
7716400	Suspension accessories for luminaires of the series: 2330...G3 .